

SECTION 1: PRODUCT INFORMATION

T.D.G. Classification Not regulated
 Product Identification Number Not available
 CAS # See "Hazardous Ingredients"
 Packing Group Not available
 Product Name Lava Melt – Ice Melt Pellets
 WHIMIS Classification Class D, Div.2, Sub. B
 Chemical Formula CaCl₂ · 2H₂O
 Product Use Ice melting
 Available Packaging 50 lb bag, 50 lb box, 40 lb pail, 2000 lb sac
 Supplier Kissner Group 32 Cherry Blossom Rd Cambridge, Ontario N3H 4R7
 (519) 650-9998
 Prepared by Jeff Browes

SECTION 2: HAZARDOUS INGREDIENTS

Hazardous Ingredients Contains Calcium Chloride Pellet. No other hazardous substances present in reportable amounts
 Percentage Not applicable
 LD/50, Route, Specie Not applicable
 LC/50, Route, Specie Not applicable

SECTION 3: PHYSICAL DATA

Physical State Solid, pellets, crystals
 Appearance & Odour Orange pellets, no odour.
 Odour Threshold Not applicable
 Specific Gravity (Water=1) 2.2
 Vapour Pressure (MMHG) (mm Hg) 0.009 @ 20 Deg C.
 Vapour Density (Air=1) Not applicable
 Evaporation Rate Not applicable
 Boiling Point 338 F 198 C
 Freezing Point -31° F
 pH 10 (1 % solution @ 20 degrees C)
 Coefficient of Water/Oil Distribution Not applicable

SECTION 4: FIRE AND EXPLOSION DATA

Hazardous Conditions See "Conditions of Reactivity". Section five.
 Fire Extinguishing Procedures Not applicable
 Flash Point Not applicable
 Upper Flammable Limit Not applicable
 Lower Flammable Limit Not applicable
 Auto-ignition Temperature Not applicable
 Hazardous Combustion Products None
 Sensitivity to mechanical impact No
 Sensitivity to Static Discharge No

SECTION 5: REACTIVITY DATA

Chemical Stability Decomposes at 350 F
 Hazardous Polymerization Not available
 Conditions of Reactivity Calcium chloride will: Corrode most metals exposed to air; attack aluminium (and its alloys) and yellow brass; react with sulphuric acid to form hydrogen chloride which is corrosive, irritating and reactive; give an exothermic reaction with water-reactive materials such as sodium; result in a runaway polymerisation reaction with methyl vinyl ether (Bretherick 1979); and, in a solution form react with zinc (galvanizing) to yield hydrogen gas which is explosive.
 Hazardous Decomposition None

SECTION 6: TOXICOLOGICAL PROPERTIES

Route of entry into the body.....	EYES, SKIN, INGESTION, INHALATION
Effects of acute exposure to product.....	EYES: May cause moderate to severe eye irritation with corneal injury, which may be slow to heal, when dissolving. The heat produced may cause more intense effects as well as thermal burns. SKIN: Not likely to cause significant skin irritation. INHALATION: Dust can be irritating. INGESTION: Single dose oral toxicity is low. Ingestion may cause gastrointestinal irritation or ulceration.
Effects of chronic exposure to product.....	SKIN: may cause skin irritation, even burn. May cause more severe response if skin is damp and/or abraded, or if material is confined to skin. When dissolving, the heat produced may cause more intense effects as well as thermal burns. EYES, INHALATION and INGESTION: see "Acute Effects" above.
Exposure limits.....	Not applicable
Irritancy of product.....	See above
Sensitization of product.....	In susceptible individuals.
Carcinogenicity of product.....	Not indicated
Reproductive toxicity.....	Not available
Teratogenicity.....	Not available
Mutagenicity.....	Not available
Synergistic effects.....	Not available
LD/50.....	900-2100 mg/kg oral, rat
LC/50.....	Not indicated

SECTION 7: PREVENTIVE MEASURES

Personal Protective Equipment required RESPIRATORY: Where exposure to dusts from this product may exceed the applicable exposure limits a NSHA-NIOSH approved respirator for the dust should be used. EYE PROTECTION: For dusty conditions, wear chemical safety goggles and hat. Under these conditions do not wear contact lenses, keep goggles clean. GLOVES: As a minimum, wear long sleeve shirt and trousers, boots and gloves for routine product use. Remove promptly any contaminated clothing. Wear safety boots.
Specific Engineering controls required..... Local exhaust ventilation.
Spill/Leak Procedures..... Losses incidental to correct application of this product in its intended use are not expected to be harmful to the environment. Wear appropriate safety apparel during clean up> avoid entry of large amounts of product into sewers, natural waters, and drinking water sources. Due to possible harmful effects, avoid contact with vegetation, animals, and fish life. Recover quickly into suitable, dry sealable containers if reusing. Small quantities may be flushed away with plenty of water. Walking surfaces may remain wet longer due to moisture being held by silled product; avoid by thoroughly water washing surfaces.
Waste Disposal..... Dispose of waste in accordance with provincial, local, and federal regulations.
Handling, Storage & Shipping Needs..... Avoid skin and eye contact. Avoid breathing dust. Remove contaminated clothing before reuse. Maintain a good personal hygiene.
Special shipping information..... Not applicable

SECTION 8: FIRST AID MEASURES

EYE CONTACT:	Flush with copious amounts of water for 15 minutes. If irritation persists consult a physician
SKIN CONTACT	Remove contaminated clothing. Wash affected area with water and soap. Seek medical attention if irritation occurs or persists.
INGESTION	If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by a medical professional.
INHALATION	Remove to fresh air.

SECTION 9: PREPARATION INFORMATION

Prepared by.....	J Browes
Emergency Phone No.	(613) 996-6666 (Canutec)
Date.....	January 2008

The information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to review this information, satisfy themselves as to its suitability and completeness and pass on the information to its employees or customers. Kissner Salt & Chemicals does not accept responsibility for any loss or damage which may occur from the use of this information.